

# quaternion 2.2.0

---

Quaternion Package for GNU Octave

Lukas F. Reichlin  
Juan Pablo Carbajal

---

Copyright © 2010-2014, Lukas F. Reichlin [lukas.reichlin@gmail.com](mailto:lukas.reichlin@gmail.com)

This manual is generated automatically from the texinfo help strings of the package's functions.

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the same conditions as for modified versions.

# Preface

The GNU Octave quaternion package from version 2 onwards was developed by Lukas F. Reichlin with important contributions by Juan Pablo Carbajal. This new package is intended as a replacement for quaternion-1.0.0 by A. Scottedward Hodel. It is loosely based on ideas from the Quaternion Toolbox for Matlab by Steve Sangwine and Nicolas Le Bihan with a special focus on code simplicity and vectorization. Its main features are:

- Matrices and n-dimensional arrays of quaternions.
- Overloaded operators due to the use of classes introduced with Octave 3.2.
- Operator semantics similar to Octave's built-in complex numbers.
- Fully vectorized code for crunching large quaternion arrays in a speedy manner.

## Using the help function

Some functions of the quaternion package are listed with the somewhat cryptic prefix `@quaternion/`. This prefix is only needed to view the help text of the function, e.g. `help norm` shows the built-in function while `help @quaternion/norm` shows the overloaded function for quaternions. Note that there are quaternion functions like `unit` that have no built-in equivalent.

When just using the function, the leading `@quaternion/` must **not** be typed. Octave selects the right function automatically. So one can type `norm (q)` and `norm (matrix)` regardless of the class of the argument.

# Table of Contents

<b>1</b>	<b>Quaternions</b>	<b>1</b>
1.1	quaternion	1
1.2	qi	1
1.3	qj	2
1.4	qk	2
1.5	q2rot	2
1.6	rot2q	3
<b>2</b>	<b>Quaternion Methods</b>	<b>4</b>
2.1	@quaternion/abs	4
2.2	@quaternion/arg	4
2.3	@quaternion/blkdiag	4
2.4	@quaternion/cast	4
2.5	@quaternion/cat	4
2.6	@quaternion/ceil	4
2.7	@quaternion/columns	4
2.8	@quaternion/conj	4
2.9	@quaternion/cumsum	5
2.10	@quaternion/diag	5
2.11	@quaternion/diff	5
2.12	@quaternion/exp	5
2.13	@quaternion/fix	5
2.14	@quaternion/floor	5
2.15	@quaternion/full	5
2.16	@quaternion/inv	6
2.17	@quaternion/isempty	6
2.18	@quaternion/isfinite	6
2.19	@quaternion/isinf	6
2.20	@quaternion/isnan	6
2.21	@quaternion/ispure	6
2.22	@quaternion/isreal	6
2.23	@quaternion/length	6
2.24	@quaternion/log	6
2.25	@quaternion/ndims	7
2.26	@quaternion/norm	7
2.27	@quaternion/reshape	7
2.28	@quaternion/round	7
2.29	@quaternion/rows	7
2.30	@quaternion/size	7
2.31	@quaternion/size_equal	8
2.32	@quaternion/sparse	8
2.33	@quaternion/squeeze	8
2.34	@quaternion/sum	8
2.35	@quaternion/tril	8
2.36	@quaternion/triu	8
2.37	@quaternion/unit	9

<b>3</b>	<b>Overloaded Quaternion Operators</b>	<b>10</b>
3.1	@quaternion/ctranspose	10
3.2	@quaternion/end	10
3.3	@quaternion/eq	10
3.4	@quaternion/ge	10
3.5	@quaternion/gt	10
3.6	@quaternion/horzcat	10
3.7	@quaternion/ldivide	10
3.8	@quaternion/le	10
3.9	@quaternion/lt	10
3.10	@quaternion/minus	10
3.11	@quaternion/mldivide	10
3.12	@quaternion/mpower	10
3.13	@quaternion/mrdivide	11
3.14	@quaternion/mtimes	11
3.15	@quaternion/ne	11
3.16	@quaternion/plus	11
3.17	@quaternion/power	11
3.18	@quaternion/rdivide	11
3.19	@quaternion/subsasgn	11
3.20	@quaternion/subsref	11
3.21	@quaternion/times	11
3.22	@quaternion/transpose	11
3.23	@quaternion/uminus	11
3.24	@quaternion/uplus	11
3.25	@quaternion/vertcat	11
	<b>Function Index</b>	<b>12</b>

# 1 Quaternions

## 1.1 quaternion

`q = quaternion (w)` [Function File]  
`q = quaternion (x, y, z)` [Function File]  
`q = quaternion (w, x, y, z)` [Function File]

Constructor for quaternions - create or convert to quaternion.

$$q = w + x*i + y*j + z*k$$

Arguments  $w$ ,  $x$ ,  $y$  and  $z$  can be scalars, matrices or  $n$ -dimensional arrays, but they must be real-valued and of equal size. If scalar part  $w$  or components  $x$ ,  $y$  and  $z$  of the vector part are not specified, zero matrices of appropriate size are assumed.

### Example

```

octave:1> q = quaternion (2)
q = 2 + 0i + 0j + 0k

octave:2> q = quaternion (3, 4, 5)
q = 0 + 3i + 4j + 5k

octave:3> q = quaternion (2, 3, 4, 5)
q = 2 + 3i + 4j + 5k

octave:4> w = [2, 6, 10; 14, 18, 22];
octave:5> x = [3, 7, 11; 15, 19, 23];
octave:6> y = [4, 8, 12; 16, 20, 24];
octave:7> z = [5, 9, 13; 17, 21, 25];
octave:8> q = quaternion (w, x, y, z)
q.w =
    2     6    10
   14    18    22

q.x =
    3     7    11
   15    19    23

q.y =
    4     8    12
   16    20    24

q.z =
    5     9    13
   17    21    25

octave:9>
  
```

## 1.2 qi

`qi` [Function File]  
 Create x-component of a quaternion's vector part.

$$q = w + x*qi + y*qj + z*qk$$

**Example**

```
octave:1> q1 = quaternion (1, 2, 3, 4)
q1 = 1 + 2i + 3j + 4k
octave:2> q2 = 1 + 2*qi + 3*qj + 4*qk
q2 = 1 + 2i + 3j + 4k
octave:3>
```

**1.3 qj****qj**

[Function File]

Create y-component of a quaternion's vector part.

$$q = w + x*qi + y*qj + z*qk$$

**Example**

```
octave:1> q1 = quaternion (1, 2, 3, 4)
q1 = 1 + 2i + 3j + 4k
octave:2> q2 = 1 + 2*qi + 3*qj + 4*qk
q2 = 1 + 2i + 3j + 4k
octave:3>
```

**1.4 qk****qk**

[Function File]

Create z-component of a quaternion's vector part.

$$q = w + x*qi + y*qj + z*qk$$

**Example**

```
octave:1> q1 = quaternion (1, 2, 3, 4)
q1 = 1 + 2i + 3j + 4k
octave:2> q2 = 1 + 2*qi + 3*qj + 4*qk
q2 = 1 + 2i + 3j + 4k
octave:3>
```

**1.5 q2rot****[axis, angle] = q2rot (q)**

[Function File]

Extract vector/angle form of a unit quaternion  $q$ .**Inputs** $q$  Unit quaternion describing the rotation.**Outputs** $axis$  Eigenaxis as a 3-d unit vector  $[x, y, z]$ . $angle$  Rotation angle in radians. The positive direction is determined by the right-hand rule applied to  $axis$ . The angle lies in the interval  $[0, 2\pi]$ .

**Example**

```

octave:1> axis = [0, 0, 1]
axis =
    0    0    1
octave:2> angle = pi/4
angle = 0.78540
octave:3> q = rot2q (axis, angle)
q = 0.9239 + 0i + 0j + 0.3827k
octave:4> [vv, th] = q2rot (q)
vv =
    0    0    1
th = 0.78540
octave:5> theta = th*180/pi
theta = 45.000
octave:6>

```

**1.6 rot2q** **$q = \text{rot2q}(\text{axis}, \text{angle})$** 

[Function File]

Create unit quaternion  $q$  which describes a rotation of  $\text{angle}$  radians about the vector  $\text{axis}$ . This function uses the active convention where the vector  $\text{axis}$  is rotated by  $\text{angle}$  radians. If the coordinate frame should be rotated by  $\text{angle}$  radians, also called the passive convention, this is equivalent to rotating the  $\text{axis}$  by  $-\text{angle}$  radians.

**Inputs**

$\text{axis}$       Vector  $[x, y, z]$  describing the axis of rotation.

$\text{angle}$       Rotation angle in radians. The positive direction is determined by the right-hand rule applied to  $\text{axis}$ .

**Outputs**

$q$       Unit quaternion describing the rotation.

**Example**

```

octave:1> axis = [0, 0, 1];
octave:2> angle = pi/4;
octave:3> q = rot2q (axis, angle)
q = 0.9239 + 0i + 0j + 0.3827k
octave:4> v = quaternion (1, 1, 0)
v = 0 + 1i + 1j + 0k
octave:5> vr = q * v * conj (q)
vr = 0 + 0i + 1.414j + 0k
octave:6>

```



## 2 Quaternion Methods

### 2.1 @quaternion/abs

`qabs = abs (q)` [Function File]  
 Modulus of a quaternion.

$$q = w + x*i + y*j + z*k$$

$$\text{abs} (q) = \sqrt{w.^2 + x.^2 + y.^2 + z.^2}$$

### 2.2 @quaternion/arg

`theta = arg (q)` [Function File]  
 Compute the argument or phase of quaternion  $q$  in radians.  $theta$  is defined as `atan2 (sqrt (q.x.^2 + q.y.^2 + q.z.^2), q.w)`. The argument  $theta$  lies in the range  $(0, \pi)$ .

### 2.3 @quaternion/blkdiag

`q = blkdiag (q1, q2, ...)` [Function File]  
 Block-diagonal concatenation of quaternions.

### 2.4 @quaternion/cast

`q = cast (q, 'type')` [Function File]  
 Convert the components of quaternion  $q$  to data type  $type$ . Valid types are int8, uint8, int16, uint16, int32, uint32, int64, uint64, double, single and logical.

### 2.5 @quaternion/cat

`q = cat (dim, q1, q2, ...)` [Function File]  
 Concatenation of quaternions along dimension  $dim$ .

### 2.6 @quaternion/ceil

`q = ceil (q)` [Function File]  
 Round quaternion  $q$  towards positive infinity.

### 2.7 @quaternion/columns

`nc = columns (q)` [Function File]  
 Return number of columns  $nc$  of quaternion array  $q$ .

### 2.8 @quaternion/conj

`q = conj (q)` [Function File]  
 Return conjugate of a quaternion.

$$q = w + x*i + y*j + z*k$$

$$\text{conj} (q) = w - x*i - y*j - z*k$$

## 2.9 @quaternion/cumsum

`q = cumsum (q)` [Function File]  
`q = cumsum (q, dim)` [Function File]  
`q = cumsum (... , 'native')` [Function File]  
`q = cumsum (... , 'double')` [Function File]  
`q = cumsum (... , 'extra')` [Function File]

Cumulative sum of elements along dimension *dim*. If *dim* is omitted, it defaults to the first non-singleton dimension. See `help cumsum` for more information.

## 2.10 @quaternion/diag

`q = diag (v)` [Function File]  
`q = diag (v, k)` [Function File]

Return a diagonal quaternion matrix with quaternion vector *V* on diagonal *K*. The second argument is optional. If it is positive, the vector is placed on the *K*-th super-diagonal. If it is negative, it is placed on the *-K*-th sub-diagonal. The default value of *K* is 0, and the vector is placed on the main diagonal. Given a matrix argument, instead of a vector, `diag` extracts the *K*-th diagonal of the matrix.

## 2.11 @quaternion/diff

`qdot = diff (q, omega)` [Function File]

Derivative of a quaternion.

Let *Q* be a quaternion to transform a vector from a fixed frame to a rotating frame. If the rotating frame is rotating about the [*x*, *y*, *z*] axes at angular rates [*wx*, *wy*, *wz*], then the derivative of *Q* is given by

$$Q' = \text{diff}(Q, \omega)$$

If the passive convention is used (rotate the frame, not the vector), then

$$Q' = \text{diff}(Q, -\omega)$$

## 2.12 @quaternion/exp

`qexp = exp (q)` [Function File]

Exponential of a quaternion.

## 2.13 @quaternion/fix

`q = fix (q)` [Function File]

Round quaternion *q* towards zero.

## 2.14 @quaternion/floor

`q = floor (q)` [Function File]

Round quaternion *q* towards negative infinity.

## 2.15 @quaternion/full

`fq = full (sq)` [Function File]

Return a full storage quaternion representation *fq* from sparse or diagonal quaternion *sq*.

## 2.16 @quaternion/inv

`qinv = inv (q)` [Function File]  
 Return inverse of a quaternion.

## 2.17 @quaternion/isempty

`bool = isempty (q)` [Function File]  
 Return true if quaternion  $q$  is empty and false otherwise.

## 2.18 @quaternion/isfinite

`bool = isfinite (q)` [Function File]  
 Return a logical array which is true where the elements of  $q$  are finite values and false where they are not.

## 2.19 @quaternion/isinf

`bool = isinf (q)` [Function File]  
 Return a logical array which is true where the elements of  $q$  are infinite and false where they are not.

## 2.20 @quaternion/isnan

`bool = isnan (q)` [Function File]  
 Return a logical array which is true where the elements of  $q$  are NaN values and false where they are not.

## 2.21 @quaternion/ispure

`bool = ispure (q)` [Function File]  
 Return true if scalar part of quaternion is zero, otherwise return false.

## 2.22 @quaternion/isreal

`bool = isreal (q)` [Function File]  
 Return true if the vector part of quaternion  $q$  is zero and false otherwise.

## 2.23 @quaternion/length

`l = length (q)` [Function File]  
 Return the "length"  $l$  of the quaternion array  $q$ . For quaternion matrices, the length is the number of rows or columns, whichever is greater (this odd definition is used for compatibility with MATLAB).

## 2.24 @quaternion/log

`qllog = log (q)` [Function File]  
 Logarithmus naturalis of a quaternion.

## 2.25 @quaternion/ndims

`n = ndims (q)` [Function File]  
 Return the number of dimensions of quaternion `q`. For any array, the result will always be larger than or equal to 2. Trailing singleton dimensions are not counted.

## 2.26 @quaternion/norm

`n = norm (q)` [Function File]  
 Norm of a quaternion.

## 2.27 @quaternion/reshape

`q = reshape (q, m, n, ...)` [Function File]  
`q = reshape (q, [m n ...])` [Function File]  
`q = reshape (q, ..., [], ...)` [Function File]  
`q = reshape (q, size)` [Function File]  
 Return a quaternion array with the specified dimensions (`m, n, ...`) whose elements are taken from the quaternion array `q`. The elements of the quaternion are accessed in column-major order (like Fortran arrays are stored).

## 2.28 @quaternion/round

`q = round (q)` [Function File]  
 Round the components of quaternion `q` towards the nearest integers.

## 2.29 @quaternion/rows

`nr = rows (q)` [Function File]  
 Return number of rows `nr` of quaternion array `q`.

## 2.30 @quaternion/size

`nvec = size (q)` [Function File]  
`n = size (q, dim)` [Function File]  
`[nx, ny, ...] = size (q)` [Function File]  
 Return size of quaternion arrays.

### Inputs

`q` Quaternion object.  
`dim` If given a second argument, `size` will return the size of the corresponding dimension.

### Outputs

`nvec` Row vector. The first element is the number of rows and the second element the number of columns. If `q` is an `n`-dimensional array of quaternions, the `n`-th element of `nvec` corresponds to the size of the `n`-th dimension of `q`.  
`n` Scalar value. The size of the dimension `dim`.  
`nx` Number of rows.  
`ny` Number of columns.  
`...` Sizes of the 3rd to `n`-th dimensions.

### 2.31 @quaternion/size\_equal

`bool = size_equal (a, b, ...)` [Function File]

Return true if quaternions (and matrices) *a*, *b*, ... are of equal size and false otherwise.

### 2.32 @quaternion/sparse

`sq = sparse (fq)` [Function File]

Return a sparse quaternion representation *sq* from full quaternion *fq*.

### 2.33 @quaternion/squeeze

`qret = squeeze (q)` [Function File]

Remove singleton dimensions from quaternion *q* and return the result. Note that for compatibility with MATLAB, all objects have a minimum of two dimensions and row vectors are left unchanged.

### 2.34 @quaternion/sum

`q = sum (q)` [Function File]

`q = sum (q, dim)` [Function File]

`q = sum (... , 'native')` [Function File]

`q = sum (... , 'double')` [Function File]

`q = sum (... , 'extra')` [Function File]

Sum of elements along dimension *dim*. If *dim* is omitted, it defaults to the first non-singleton dimension. See `help sum` for more information.

### 2.35 @quaternion/tril

`q = tril (q)` [Function File]

`q = tril (q, k)` [Function File]

`q = tril (q, k, 'pack')` [Function File]

Return a new quaternion matrix formed by extracting the lower triangular part of the quaternion *q*, and setting all other elements to zero. The second argument *k* is optional, and specifies how many diagonals above or below the main diagonal should also be included. Default value for *k* is zero. If the option "pack" is given as third argument, the extracted elements are not inserted into a matrix, but rather stacked column-wise one above other.

### 2.36 @quaternion/triu

`q = triu (q)` [Function File]

`q = triu (q, k)` [Function File]

`q = triu (q, k, 'pack')` [Function File]

Return a new quaternion matrix formed by extracting the upper triangular part of the quaternion *q*, and setting all other elements to zero. The second argument *k* is optional, and specifies how many diagonals above or below the main diagonal should also be included. Default value for *k* is zero. If the option "pack" is given as third argument, the extracted elements are not inserted into a matrix, but rather stacked column-wise one above other.

### 2.37 @quaternion/unit

`qn = unit (q)`

[Function File]

Normalize quaternion to length 1 (unit quaternion).

```
q = w + x*i + y*j + z*k
```

```
unit (q) = q ./ sqrt (w.^2 + x.^2 + y.^2 + z.^2)
```

## 3 Overloaded Quaternion Operators

### 3.1 @quaternion/ctranspose

Conjugate transpose of a quaternion. Used by Octave for "q'".

### 3.2 @quaternion/end

End indexing for quaternions. Used by Octave for "q(1:end)".

### 3.3 @quaternion/eq

Equal to operator for two quaternions. Used by Octave for "q1 == q2".

### 3.4 @quaternion/ge

Greater-than-or-equal-to operator for two quaternions. Used by Octave for "q1 >= q2". The ordering is lexicographic.

### 3.5 @quaternion/gt

Greater-than operator for two quaternions. Used by Octave for "q1 > q2". The ordering is lexicographic.

### 3.6 @quaternion/horzcat

Horizontal concatenation of quaternions. Used by Octave for "[q1, q2]".

### 3.7 @quaternion/ldivide

Element-wise left division for quaternions. Used by Octave for "q1 ./ q2".

### 3.8 @quaternion/le

Less-than-or-equal-to operator for two quaternions. Used by Octave for "q1 <= q2". The ordering is lexicographic.

### 3.9 @quaternion/lt

Less-than operator for two quaternions. Used by Octave for "q1 < q2". The ordering is lexicographic.

### 3.10 @quaternion/minus

Subtraction of two quaternions. Used by Octave for "q1 - q2".

### 3.11 @quaternion/mldivide

Matrix left division for quaternions. Used by Octave for "q1 \ q2".

### 3.12 @quaternion/mpower

Matrix power operator of quaternions. Used by Octave for "q^x".

### 3.13 @quaternion/mrdivide

Matrix right division for quaternions. Used by Octave for " $q_1 / q_2$ ".

### 3.14 @quaternion/mtimes

Matrix multiplication of two quaternions. Used by Octave for " $q_1 * q_2$ ".

### 3.15 @quaternion/ne

Not-equal-to operator for two quaternions. Used by Octave for " $q_1 \neq q_2$ ".

### 3.16 @quaternion/plus

Addition of two quaternions. Used by Octave for " $q_1 + q_2$ ".

### 3.17 @quaternion/power

Power operator of quaternions. Used by Octave for " $q.^x$ ". Exponent  $x$  can be scalar or of appropriate size.

### 3.18 @quaternion/rdivide

Element-wise right division for quaternions. Used by Octave for " $q_1 ./ q_2$ ".

### 3.19 @quaternion/subasgn

Subscripted assignment for quaternions. Used by Octave for " $q.\text{key} = \text{value}$ ".

### 3.20 @quaternion/subsref

Subscripted reference for quaternions. Used by Octave for " $q.w$ ".

### 3.21 @quaternion/times

Element-wise multiplication of two quaternions. Used by Octave for " $q_1 .* q_2$ ".

### 3.22 @quaternion/transpose

Transpose of a quaternion. Used by Octave for " $q.'$ ".

### 3.23 @quaternion/uminus

Unary minus of a quaternion. Used by Octave for " $-q$ ".

### 3.24 @quaternion/uplus

Unary plus of a quaternion. Used by Octave for " $+q$ ".

### 3.25 @quaternion/vertcat

Vertical concatenation of quaternions. Used by Octave for " $[q_1; q_2]$ ".





# Function Index

## A

abs .....	4
arg .....	4

## B

blkdiag .....	4
---------------	---

## C

cast .....	4
cat .....	4
ceil .....	4
columns .....	4
conj .....	4
ctranspose .....	10
cumsum .....	5

## D

diag .....	5
diff .....	5

## E

end .....	10
eq .....	10
exp .....	5

## F

fix .....	5
floor .....	5
full .....	5

## G

ge .....	10
gt .....	10

## H

horzcat .....	10
---------------	----

## I

inv .....	6
isempty .....	6
isfinite .....	6
isinf .....	6
isnan .....	6
ispure .....	6
isreal .....	6

## L

ldivide .....	10
le .....	10
length .....	6
log .....	6
lt .....	10

## M

minus .....	10
mldivide .....	10
mpower .....	10
mrdivide .....	11
mtimes .....	11

## N

ndims .....	7
ne .....	11
norm .....	7

## P

plus .....	11
power .....	11

## Q

q2rot .....	2
qi .....	1
qj .....	2
qk .....	2
quaternion .....	1

## R

rdivide .....	11
reshape .....	7
rot2q .....	3
round .....	7
rows .....	7

## S

size .....	7
size_equal .....	8
sparse .....	8
squeeze .....	8
subsasgn .....	11
subsref .....	11
sum .....	8

## T

times .....	11
transpose .....	11
tril .....	8
triu .....	8

## U

uminus .....	11
unit .....	9
uplus .....	11

## V

vertcat .....	11
---------------	----